



iSelf VENDING

It's now easier than ever before to make payments at an unattended point of sale.

The automated terminals from SIX with the state-of-the-art PCI 4.x standard.

The new iSelf terminal line from Ingenico is ideal for indoor and outdoor deployment and at any location where payments need to be accepted at unattended points of sale. The iSelf terminals, which are weather-resistant and extremely robust, are available in a choice of two models:

iSelf VENDING Classic – The full-service payment terminal

This product consists of a PinPad (keypad), a slot reader and a contactless reader.

iSelf Classic can be used in any sector and is suitable especially for high frequency areas.



iSelf VENDING Air – The simple contactless-only payment terminal

This terminal solely features a contactless module and is used on machines with comparatively low transaction amounts to enable quick and easy payment processing. For regulatory reasons, this terminal is only suitable for certain sectors and uses.



	iSelf VENDING Classic Pinpad	Slot reader	Contactless reader	iSelf VENDING Air Contactless module
				
Processor	Risc 32-bits ARM9	Risc 32-bits ARM7	Risc 32-bits ARM7	Risc 32-bits ARM9
Memory	32 MB RAM/128 MB Flash	96 KB RAM/512 KB Flash	96 KB RAM/512 KB Flash	32 MB RAM/128 MB Flash
Display	Resolution 128 × 64 pixels, RGB background lighting	Not applicable	RVB background lighting area, 4 green LEDs	Resolution 128 × 64 pixels, RGB background lighting, RVB background lighting area, 4 green LEDs
Keypad	15 buttons with embossed symbols, back-lit	Not applicable	Not applicable	2 capacitive buttons
Card reader	Not applicable	Smart card hybrid magstripe	NFC/contactless	NFC/contactless
Communication	Ethernet	USB	USB	Ethernet
Power supply	9–16 V max – 2 A mA	5 V max – 500 mA with USB slave	5 V max – 500 mA with USB slave	10–45 V max – 2 A mA
Dimensions B × H × D mm	101 × 134 × 39 mm	108 × 73 × 148 mm	73 × 61 × 23 mm	103 × 135 × 62 mm
Cut area B × H mm	85 × 107 mm	74 × 62 mm	16 × 25 mm	85 × 107 mm
Weight	860 g	700 g	87 g	620 g
PCI version	4.x	4.x	4.x	3.x
Ambient conditions	Operating temperature –20 °C to +65 °C Storage temperature –20 °C to +65 °C Relative humidity, no thawing 85% RH at +55 °C IP ingress protection IP65 Shock protection IK10	Operating temperature –20 °C to +65 °C Storage temperature –20 °C to +65 °C Relative humidity, no thawing 85% RH at +55 °C IP ingress protection IP34 Shock protection IK10	Operating temperature –20 °C to +65 °C Storage temperature –20 °C to +65 °C Relative humidity, no thawing 95% RH at +55 °C IP ingress protection IP65 Shock protection IK10	Operating temperature –20 °C to +65 °C Storage temperature –20 °C to +65 °C Relative humidity, no thawing 90% RH at +55 °C IP ingress protection IP65 Shock protection IK10

Your local point of contact can be found at: www.six-payment-services.com/contact

SIX Payment Services Ltd
Hardturmstrasse 201
P.O. Box
CH-8021 Zurich

SIX Payment Services (Europe) S.A.
10, rue Gabriel Lippmann
5365 Munsbach
Luxembourg

SIX Payment Services (Austria) GmbH
Marxergasse 1B
1030 Vienna
Austria

