

iSELF VENDING

SIMPLE PAYMENTS AT UNATTENDED POINTS OF SALE

Ideal for indoor and outdoor use and for payments at unattended points of sale. The iSelf VENDING terminals are weather resistant and extremely robust. Two models are available:

**iSELF VENDING CLASSIC –
THE FULL-SERVICE PAYMENT TERMINAL**

This product consists of a pinpad (keypad), a slot reader and a contactless reader.

iSelf Classic can be used in any sector and is suitable especially for high frequency areas.

**iSELF VENDING AIR –
THE CONTACTLESS-ONLY
PAYMENT TERMINAL**

This terminal solely features a contactless module and is used on machines with comparatively low transaction amounts to enable quick and easy payment processing. For regulatory reasons, this terminal is only suitable for certain sectors and uses.



TECHNICAL DETAILS

iSELF VENDING CLASSIC PINPAD



SLOT READER



CONTACTLESS READER



iSELF VENDING AIR CONTACTLESS MODULE



| | | | | |
|--|---|---|---|---|
| Processor | RISC 32-bit ARM9 | RISC 32-bit ARM7 | RISC 32-bit ARM7 | RISC 32-bit ARM9 |
| Memory | 32 MB RAM/128 MB Flash | 96 KB RAM/512 KB Flash | 96 KB RAM/512 KB Flash | 32 MB RAM/128 MB Flash |
| Display | Resolution 128 × 64 pixels, RGB background lighting | Not applicable | RVB background lighting area, 4 green LEDs | Resolution 128 × 64 pixels, RGB background lighting, RVB background lighting area, 4 green LEDs |
| Keypad | 17 buttons | Not applicable | Not applicable | 16 buttons for maintenance |
| Card reader | Not applicable | Smart card hybrid magstripe | NFC/contactless | NFC/contactless |
| Communication | Ethernet | USB | USB | Ethernet |
| Power supply | 9–16 V Max / 2 A | UBS 5 V / 500 mA USB slave | UBS 5 V / 500 mA USB slave | 10–45 V Max / 2 A |
| Dimensions B × H × D mm Cut area B × H mm | 101 × 134 × 39 mm 86.4 × 108.7 mm | 108 × 73 × 148 mm 74 × 62 mm | 73 × 61 × 23 mm 16 × 25.5 mm | 103 × 135 × 65 mm 86.4 × 108.7 mm |
| Weight | 860 g | 700 g | 87 g | 700 g |
| PCI version | 4.x | 4.x | 4.x | 3.x |
| Ambient conditions | Operating temperature –20 °C to +55 °C Storage temperature –20 °C to +65 °C Relative humidity, no thawing 85% RH at +55 °C IP ingress protection IP65 Shock protection IK10 | Operating temperature –20 °C to +65 °C Storage temperature –20 °C to +65 °C Relative humidity, no thawing 85% RH at +55 °C IP ingress protection IP34 Shock protection IK10 | Operating temperature –20 °C to +65 °C Storage temperature –20 °C to +70 °C Relative humidity, no thawing 95% RH at +55 °C IP ingress protection IP65 Shock protection IK10 | Operating temperature –20 °C to +65 °C Storage temperature –20 °C to +65 °C Relative humidity, no thawing 85% RH at +55 °C IP ingress protection IP65 Shock protection IK10 |

YOUR LOCAL POINT OF CONTACT CAN BE FOUND AT:
six-payment-services.com/contacts

six-payment-services.com
worldline.com