

ENGAGE MOBILE

THE ALL-ROUND TERMINAL FOR GREATER FLEXIBILITY IN EVERYDAY LIFE

With the Engage MOBILE, you can offer your customers maximum flexibility when they pay. The compact terminal is characterised by a fast and reliable connection at any location.

COMPACT AND HANDY





















ENGAGE MOBILE WLAN

ENGAGE MOBILE FLEX





Dimensions (L× W× H)	160.75 × 72.85 × 59 mm	160.75 × 72.85 × 59 mm
Weight	412 g	412 g
Memory	1024 MB (512 MB Flash, 512 MB SDRAM)	1024 MB (512 MB Flash, 512 MB SDRAM)
Processors	600 MHzCortex A9 32-bit RISC Processor	600 MHz Cortex A9 32-bit RISC Processor
Display	 3.5" LCD colour display 320 × 480 pixels (HVGA) Slightly angled touchscreen display 	 3.5" LCD colour display 320 × 480 pixels (HVGA) Slightly angled touchscreen display
Printer	Thermal printer, 30 lines/second, 40 mm paper roll	Thermal printer, 30 lines/second, 40 mm paper roll
Approvals	EMC Level 1 and 2, PCI PTS 5.x, SRED	EMC Level 1 and 2, PCI PTS 5.x, SRED
Communication	WLAN 2.4 GHz & 5 GHz	4G, WLAN 2.4 GHz & 5 GHz
Cash register connection	Optional (ENGAGE MOBILE PINPAD)	-
Keypad	15 backlit keys with high abrasion resistanceKeypad corresponds to EBS100	15 backlit keys with high abrasion resistanceKeypad corresponds to EBS100
Card reader	 3 track magnetic stripe reader according to ISO7810, ISO7811, ISO7813 Chip card reader according to ISO7816-3, ISO7816-10 with 1.8 V, 3 V and 5 V EMVCo 4.0 Level certified 	 3 track magnetic stripe reader according to ISO7810, ISO7811, ISO7813 Chip card reader according to ISO7816-3, ISO7816-10 with 1.8 V, 3 V and 5 V EMVCo 4.0 Level certified
Contactless function	 Contactless reader according to ISO14443 A ISO14443B, ISO18092 compatible Supports the most important NFC/ contactless systems 	 Contactless reader according to ISO14443 A ISO14443B, ISO18092 compatible Supports the most important NFC/ contactless systems
Ambient conditions	 Operating temperature: 0° to 50°C Storage temperature: -20° to 60°C Relative humidity: 5% to 95% Non-condensing 	 Operating temperature: 0° to 50°C Storage temperature: -20° to 60°C Relative humidity: 5% to 95% Non-condensing
Accessories	Spare battery, base station (charger) 5 V DC, 2.2 A	Spare battery, base station (charger) 5 V DC, 2.2 A

YOUR LOCAL POINT OF CONTACT CAN BE FOUND AT:

six-payment-services.com/contacts

six-payment-services.com worldline.com



















