

The intuitive terminal with touch function

yomani touch XR

Take advantage of the efficient, reliable payment service from SIX Payment Services. Because quality matters.

Thanks to its fast data processing, clear user interface and elegant design, the yomani touch XR is the ideal terminal for payments at all points of sale.

The touch screen and the integrated NFC reader on the side of the terminal contribute to the positive customer experience.

Your advantages at a glance

- ✓ Touch screen for enhanced user-friendliness
- ✓ Contactless function to make payments even quicker
- ✓ Full card acceptance for increased customer satisfaction
- ✓ Additional value-added solutions available, such as Dynamic Currency Conversion (DCC)



Contactless



Mobile
Payment



Security
Standard



Printer
(COMPACT)



Touch
Display

Product versions

yomani touch XR PINPAD	yomani touch XR AUTONOM	yomani touch XR COMPACT
		
Terminal for integrated operation	Combination of PINPAD and merchant unit for autonomous operation	PINPAD terminal with printer for integrated operation

Technical specifications

	yomani touch XR PINPAD	Merchant unit for yomani touch XR AUTONOM	yomani touch XR COMPACT
Dimensions (l x w x h)	170 x 116 x 105 mm	228 x 91 x 68 mm	230 x 116 x 105 mm
Weight	650 g	309 g	800 g
Communication	LAN	USB connection between the terminal unit and merchant unit	LAN
Power supply	External power unit	External power unit	External power unit
Display (pixels)	Colour display 320 x 240	LCD display 128 x 64	Colour display 320 x 240
Screen size	3,5"	3,2"	3,5"
Thermal printer	–	Yes – receipt printing from the merchant unit	Yes – receipt printing from the terminal
Security certificate	PCI PTS 5.x	–	PCI PTS 5.x
Point of sale integration	MPD/TIM	–	MPD/TIM
Card reader	EMV chip Magnetic strip Contactless	–	EMV chip Magnetic strip Contactless
Ambient conditions	– Operating temperature: 0 °C to 50 °C – Storage temperature: –10 °C to 60 °C – Relative humidity: 5% to 90% – No thawing	– Operating temperature: 0 °C to 50 °C – Storage temperature: –10 °C to 60 °C – Relative humidity: 5% to 90% – No thawing	– Operating temperature: 0 °C to 50 °C – Storage temperature: –10 °C to 60 °C – Relative humidity: 5% to 90% – No thawing
Options	Fixing panel Assembly stand	–	Fixing panel Rotary plate Assembly stand

Your local point of contact can be found at: www.six-payment-services.com/contact

SIX Payment Services Ltd
Hardturmstrasse 201
8021 Zurich
Switzerland

SIX Payment Services (Europe) S.A.
10, rue Gabriel Lippmann
5365 Munsbach
Luxembourg

SIX Payment Services (Europe) S.A.
Austrian branch
Marxergasse 1B
A-1030 Vienna

SIX Payment Services (Europe) S.A.
German branch
Franklinstrasse 61-63
D-60486 Frankfurt/Main