



DAVINCI III VENDING

# Reliable payments for vending machines

The ideal terminal for internal and external use and payments at unattended points of sale.

Paying for tickets, parking tickets and other services at vending machines has never been so easy and so secure. davinci III Vending is weather-resistant and extremely robust and is therefore ideal for payments at petrol stations as well as for park and card vending machines.

The combination of pinpad (keypad), slot reader and contactless reader is customer-friendly to use and enables fast contactless payment and payments with chip.

## IDEAL FOR INTERNAL AND EXTERNAL USE

davinci III Vending is a secure and reliable solution for vending machines:

- High-end terminal for unattended points of sale
- Latest PCI PTS 5.x security standard
- Reliable and robust
- Contactless payments for even faster payment
- Protection against vandalism
- Same dimensions as with the previous model, no adaptation required
- Acceptance of petrol cards



CONTACTLESS



MOBILE  
PAYMENTS



PETROL  
SUPPORT

# Technical details

## DAVINCI III VENDING PINPAD



## SLOT READER



## CONTACTLESS READER



<b>Processors</b>	32 Bit ARM application processor 32 Bit ARM security processor	Not applicable	Not applicable
<b>Storage</b>	64 MB RAM 128 MB Flash	Not applicable	Not applicable
<b>Display</b>	TFT colour display 320 × 240 pixels High level of brightness and high contrast, readable in sunlight	Not applicable	Not applicable
<b>Keypad</b>	Yes	Not applicable	Not applicable
<b>Card reader</b>	Not applicable	Smart Card Hybrid, Magstripe	NFC/contactless
<b>Communication</b>	10/100 Mbit Ethernet	Not applicable	Not applicable
<b>Power supply</b>	Supply via card reader	12 V AC or 14–36 V DC	Supply via Pinpad
<b>Dimensions W × H × D mm</b>	80 × 120 × 40 mm	81 × 73 × 139 mm	82 × 80 × 36 mm
<b>Required space W × H mm</b>	80.5 × 120.5 mm	68 × 50 mm	63 × 73 mm
<b>Weight</b>	540 g	725 g	212 g
<b>PCI version</b>	PCI-PTS 5.x	PCI-PTS 5.x	PCI-PTS 5.x
<b>Ambient conditions</b>	–20 °C to +70 °C 0–85% humidity (non-condensing)	–20 °C to +70 °C 0–85% humidity (non-condensing)	–20 °C to +70 °C 0–85% humidity (non-condensing)
<b>Level of protection</b>	IP65, IK10	IP34, IK10	IP65, IK10

Your local point of contact can be found at: [worldline.com/merchant-services/contacts](https://worldline.com/merchant-services/contacts)

