

ENGAGE PINPAD

THE POWERFUL INTEGRATED TERMINAL

The Engage PINPAD is the ideal reliable solution for processing all standard credit and debit cards and mobile payment solutions via your cash register system.

With ultra-fast data processing, an interactive user interface and modern design, the Engage PINPAD is the optimal terminal for handling cashless payments via your cash register system.

The slightly angled colour display with touchscreen function and integrated NFC reader provides even more convenience during operation.

POWERFUL AND INNOVATIVE

The Engage PINPAD is a secure and reliable solution for your business:

- Can be integrated into any cash register infrastructure
- Touchscreen display for a more user-friendly experience
- Contactless function for faster payment
- Seamless card acceptance for greater customer satisfaction
- Added value solutions such as DCC (Dynamic Currency Conversion) available
- PCI PTS 5.x security standard



Contactless

Mobile
PaymentSecurity
Standard

Printer

TECHNICAL SPECIFICATIONS

ENGAGE PINPAD



Dimensions (L × W × H)	167 × 80 × 44 mm
Weight	310 g
Memory	1024 MB (512 MB Flash, 512 MB SDRAM)
Processors	<ul style="list-style-type: none"> • 600 MHz • Cortex A9 32-bit RISC Processor
Display	<ul style="list-style-type: none"> • 3.5" LCD colour display 320 × 480 pixels (HVGA) • Slightly angled touchscreen display
Printer	–
Approvals	EMC Level 1 and 2, PCI PTS 5.x, SRED
Communication	LAN/WLAN
Cash register connection	Yes
Keypad	<ul style="list-style-type: none"> • 15 backlit keys with high abrasion resistance • Keypad corresponds to EBS100
Card reader	<ul style="list-style-type: none"> • 3 track magnetic stripe reader according to ISO7810, ISO7811, ISO7813 • Chip card reader according to ISO7816-3, ISO7816-10, 3 V and 5 V, EMVCo 4.0 Level certified
Contactless function	<ul style="list-style-type: none"> • Contactless reader according to ISO1444 • ISO14443B, ISO18092 compatible • Supports the most important NFC/contactless systems
Ambient conditions	<ul style="list-style-type: none"> • Operating temperature: 0 ° to 50 °C • Storage temperature: -20 ° to 60 °C • Relative humidity: 5% to 95% • Non-condensing
Accessories	Mounting fixtures specially adapted to the terminal

YOUR LOCAL POINT OF CONTACT CAN BE FOUND AT:
six-payment-services.com/contacts

six-payment-services.com
 worldline.com